


ITEM	PART NAME	MATERIAL	QTY
1	BODY	BRASS CDA-360	1
2	SEAT INSERT	PCTFE	1
3	DIAPHRAGM ASSY.	316L SST/COPPER	1
4	BONNET	303 SST	1
5	STEM	416 SST	1
6	POSITIONER LOCK NUT	CHROME PLATED BRASS CDA-360	1
7	WASHER	18-8 SST	1
8	SCREW	18-8 SST	1
9	HANDLE	ALUMINUM T-6061	1
10	STOP PIN	18-8 SST	1
11	COLLAR	ALUMINUM 2011 T-3	1
12	POSITIONER GLAND	CHROME PLATED BRASS CDA-360	1
13	LABEL	VINYL/MYLAR	1



UNCONTROLLED
For Reference Only
MB 3/30/2007

SPECIFICATIONS:
 PRESSURE RATING: 3500 PSI
 FLOW COEFFICIENT Cv = .13
 SEAT ORIFICE SIZE: .125 ϕ
 SEAT MATERIAL: PCTFE
 TEMPERATURE LIMITS:
 -65° F TO 150° F
 MAX. ALLOWABLE SEAT LEAKAGE:
 2 x 10-8 ATM CC/SEC He
 MAX. INBOARD LEAKAGE:
 2 x 10-8 ATM CC/SEC He
 WETTED SURFACES: PCTFE,
 BRASS CDA-360.

GasFlo Products Inc.
 Fairfield, N.J.

SALES DRAWING- LONG LEG QUARTER TURN BRASS

1/4 MALE NPT x 1/4 FEMALE NPT PACKLESS BARSTOCK VALVE

NOTES:
 1. HANDLE SHOWN IN OPEN POSITION.

THIS DOCUMENT CONTAINS INFORMATION THAT IS THE PROPRIETARY AND CONFIDENTIAL PROPERTY OF GASFLO PRODUCTS INC. AND MAY BE USED ONLY FOR AUTHORIZED PURPOSES. THIS DOCUMENT MAY NOT BE REPRODUCED WITHOUT GASFLO PRODUCTS INC. PRIOR WRITTEN CONSENT

DWN	MB	SCALE: 1:1
APPVD		DATE 8/21/02

DWG	SALES-VLV-QLL-44BR-MF
-----	-----------------------