



ITEM	PART NAME	MATERIAL	QTY
1	BODY	316L SST	1
2	SEAT INSERT	PCTFE	1
3	DIAPHRAGM ASSY.	316L SST/COPPER	1
4	BONNET	303 SST	1
5	STEM	416 SST	1
6	POSITIONER LOCK NUT	CHROME PLATED BRASS CDA-360	1
7	WASHER	18-8 SST	1
8	SCREW	18-8 SST	1
9	HANDLE	ALUMINUM-- NOTE 2	1
10	STOP PIN	ALLOY STEEL	1
11	COLLAR	ALUMINUM	1
12	POSITIONER GLAND	CHROME PLATED BRASS CDA-360	1
13	LABEL	VINYL/MYLAR	1

SPECIFICATIONS:
 PRESSURE RATING: 3500 PSI
 FLOW COEFFICIENT Cv = .13
 SEAT ORIFICE SIZE: .125 ϕ
 SEAT MATERIAL: PCTFE
 TEMPERATURE LIMITS:
 -65° F TO 150° F
 MAX. INBOARD LEAKAGE:
 2 x 10-8 ATM CC/SEC He
 WETTED SURFACES: PCTFE,
 316L SST.

GasFlo Products Inc.
 Fairfield, N.J.

- NOTES:
 1. DIMENSIONS ARE IN INCHES.
 2. HANDLE TO BE CLEAR ANODIZED.

2x.190-32UNF-2B THREAD

THIS DOCUMENT CONTAINS INFORMATION THAT IS THE PROPRIETARY AND CONFIDENTIAL PROPERTY OF GASFLO PRODUCTS INC. AND MAY BE USED ONLY FOR AUTHORIZED PURPOSES. THIS DOCUMENT MAY NOT BE REPRODUCED WITHOUT GASFLO PRODUCTS INC. PRIOR WRITTEN CONSENT

DWN MB SCALE: 1:1
 APPVD DATE 8/14/02

QUARTER TURN REAR PANEL MOUNT PACKLESS BARSTOCK VALVE
 SALES DRAWING- 1/4" x 1/4" TUBE WELD
 DWG SALES-VLV-QSL-44SS-TSTS